





Off-Street Blister Tactiles



GRIPFAST Off-Street Blister Tactiles are designed to warn visually impaired people of the presence of an edge of a railway platform.

GRIPFAST Off-Street Blister Tactiles are manufactured from a durable GRP (glass reinforced polyester) panel. The panel surface comprises offset rows of flat-topped 'blisters' 5mm high, spaced 66.5mm apart from the centre of one blister to the centre of the next. Each blister contains a near-diamond-hard aggregate which gives it an anti slip surface profile and ensures a long life span.

GRIPFAST Off-Street Blister tactiles can be supplied in an almost infinite number of colours and are suitable for use on timber, concrete, flat steel, tarmac and asphalt substrates. They are suitable for external use and are resistant to frost, oil, grease and most chemicals. They are designed to be bonded and mechanically fixed to a structurally sound and level substrate and will provide a guaranteed slip resistant surface for up to 30 years.



Product Benefits

- Installation of product ensures compliance with current DDA (Disability Discrimination Act) and Building Regulations
- Available in an infinite number of colours ensures that the tactiles can be optimally matched to the environment.
- Anti slip properties meet the UK guidelines for slip resistance, minimising the risk of slip accidents.
- Design life guarantee of thirty years ensures a long life for an installation
- Tactiles conform to all current DETR guidelines.
- Tactiles can be cut easily with a diamond-tipped blade to match up to the required area.
- Option to have chamfered leading edge eliminates the risk of trips.
- Can be glued and/or screwed down to virtually any surface eliminating the need for time-consuming and costly excavation

Product Thickness

- 4mm or 6mm base plus 5mm high blisters. Each tactile can be chamfered to avoid a trip hazard or incorporated into a complete platform panel design.

Colours

- Any BS or RAL colour available

Standard size

- Tactiles are always 400mm deep and are supplied by the linear metre run - usually 1200mm or 1220mm sections.

POLYDECK LTD
Unit 14, Burnett Industrial Estate
Cox's Green
Wrington
Bristol
BS40 5QS